

Rinnai



Hotflo Plus

Electric Storage Systems - QLD & WA

Benefits at a glance



Hot water all year round

Our hardworking range of Hotflo Plus Electric Hot Water Storage Systems provide a variety of features such as flexible installation options, Vitreous Enamel lined tanks and a generous 12 year extended cylinder warranty. Rinnai Hotflo Plus Electric storage systems are available in various capacities. From our super compact 25 litre unit, through to our super sized 400 litre storage cylinder, these tanks are perfect for replacing an existing unit.

We're at your service

The National Customer Care Centre provides first class service and maintenance of your system, ensuring it's running at its highest efficiency - so you can enjoy the Rinnai experience for many years to come.

Operating 5 days a week
(Monday to Friday)

13 43 73



Features and Benefits



Warranty

7 year cylinder warranty on 25L and 50L models.
12 Year extended cylinder warranty on 80L to 400L models*.



Quality

Class leading Rinnai quality and durability.



Elements

Single configurations. Complete range of single elements.



Range

Full range of capacities to suit all applications
25 to 400 litres.



Location

80L to 400L models suitable for internal and external installations.



Connectability

Standard sizing perfect for emergency changeover with dual handed for flexible installation.


Sizing Guide

Tank size	No. of persons - Peak electric (Continuous tariff)		No. of persons - Off peak electric	
	Warm climate	Cool climate	Warm climate	Cool climate
50 Litres	1	1	Not recommended	Not recommended
80 Litres	2 to 3	1 to 2	1 to 2	Not recommended
125 Litres	3 to 4	2 to 3	2 to 3	1 to 2
160 Litres	4 to 5	3 to 4	3 to 4	2 to 3
250 Litres	7 to 8	5 to 6	5 to 6	4 to 5
315 Litres	8 to 9	6 to 7	6 to 7	5 to 6
400 Litres	8 to 9	8+	8+	6+

*For full terms & conditions visit www.plumbingplus.com.au

Technical Information

	Hotflo 25L	Hotflo 25L Plug-in	Hotflo 50L	Hotflo 50L Plug-in	Hotflo 80L	Hotflo 125L	Hotflo 160L	Hotflo 250L	Hotflo 315L	Hotflo 400L
Storage Capacity (L)	33	33	55	55	84	140	179	271	336	424
Hot Water Delivery (L)	25	25	50	50	80	125	160	250	315	400
Element Size (kW)	3.6	2.4	3.6	2.4	2.4, 3.6	1.8, 3.6	2.4, 3.6	3.6, 4.8	3.6, 4.8	3.6, 4.8
Total Height (mm)	A	452	452	694	452	900	1245	1530	1475	1820
Width incl. PTR Valve (mm)		490	490	490	490	590	590	590	700	700
Diameter (mm)	B	415	415	415	415	515	515	515	625	625
Outlet Height (mm)	C	297	297	524	524	685	1020	1310	1215	1430
Inlet Height (mm)	D	153	153	158	158	225	225	225	90	90
Electrical Entry - Lower (mm)	E	80	80	80	80	155	155	155	50	50
Packaged Weight (kg)		23	23	29	29	48	60	71	93	109
Included PTR Valve (kPa)						1000				850
ECV (kPa)						850				700
Max. Inlet Pressure with ECV (kPa)						680				550
PLV with ECV (kPa)						500				500
Max. Inlet Pressure without ECV (kPa)						800				680
PLV without ECV (kPa)						500				500
Max. Thermostat Setting (°C)						70				70
Ingress Protection Rating						IPX4				IPX4
Electrical Supply						240V - @50Hz				240V - @50Hz
Hot and cold water connection						Rp ³ / ₄ (20mm)				Rp ³ / ₄ (20mm)
Tank Body Colour			White						Dune	



In accordance with our policy of continuous improvement, Rinnai Australia reserves the right to make modifications, change specifications or discontinue models at any time without notice, however, we will endeavour to communicate major changes before implementation. Dimensions are subject to production tolerances and may vary slightly from those given. For full definitions of domestic and commercial use along with the full warranty conditions and exclusions, please refer to the owners manual. The images reproduced in this brochure are for illustrative purposes only, are not to scale and may vary in colour to those of the represented product.

Rinnai Australia Pty Ltd

ABN 74 005 138 769

100 Atlantic Drive,
Keysborough, Victoria 3173

For further information
call 1300 555 545 or visit
rinnai.com.au

TOTAL HOME COMFORT



HOT WATER



HEATING



COOLING

Rinnai